



SBR 直线支撑轴 Supported Steel Shafts



产品特性 Product Features

- 材料 Material: SCS 高精度直线轴配合铝制支撑
SCS precision steel shafts with stangardaluminum
- support
- 高承载 High load
- 高精度 High precision
- 低成本 Low cost

Special shafts can be manufactured according to your requirement. Please contact with us.

标准规格 Standard Size Sheet

订购编码 Order P/N	直径 Φ mm ²	公差 Tolerance g6	标准长度 Standard Length mm ²	最大长度 Max.Length mm ²	N mm ²	P mm ²	硬化厚度 Hardening Depth mm ²	重量 Weight kg/m
SBR-16	16	-0.006/+0.017	190 340 640 940	3000	20	150	1.00	1.58
SBR-20	20	-0.007/+0.020	340 640 940 1240	3000	20	150	1.50	2.47
SBR-25	25	-0.007/+0.020	250 450 850 1250	3000	25	200	1.50	3.85
SBR-30	30	-0.007/+0.020	450 850 1250 1450	3000	25	200	1.50	5.55
SBR-40	40	-0.009/+0.025	460 660 860 1060 1260	3000	30	200	2.00	9.87
SBR-50	50	-0.009/+0.025	470 670 870 1070 1270	3000	35	200	2.00	15.40

订购编码 Order P/N	直径 Φ mm ²	尺寸 Size (mm ²)										
		E	h	B	H	T	F	X	Y	C	S1	S2 d1 × d2 × l
SBR-16	16	20	25	40	17.8	5	18.5	8	11.7	30	5.5	5.5 × 9.5 × 5.4
SBR-20	20	22.5	27	45	17.7	5	19	8	10	30	5.5	5.5 × 9.5 × 5.4
SBR-25	25	27.5	33	55	21	6	21.5	8	12	35	6.6	6.6 × 11 × 6.5
SBR-30	30	30	37	60	22.8	7	26.5	10.3	13	40	6.6	6.6 × 11 × 6.5
SBR-40	40	37.5	48	75	29.5	9	38	15.5	17	55	9	9 × 14 × 8.6
SBR-50	50	47.5	62	95	38.8	11	45	20	21	70	11	111 × 7.5 × 10.8

订购编码 Order P/N:

SCS-06-1000

